



Straight Connector



Endstop Connector

Microfit Couplers

Designed specifically for FTTx applications, the Condux® Microfit Couplers combine ease of use, chemical resistance and ability to accommodate the high pressures encountered when installing fiber with micro-blowing equipment.

The transparent design ensures proper attachment by allowing the installer to visually verify that each end of the duct has been seated properly inside the coupler. Once connected, the air and water tight seal will hold pressure up to 232 PSI (16 Bar) in temperatures ranging from -4°F to 140°F (-20°C to 60°C).

These features incorporated into a push-on, no tools required design, make the Condux® Microfit Coupler an essential component of the professional installers toolbox.

ISO 9001:2008
CERTIFIED

Part Number	Description	Part Number	Description
08566310	Straight Connector - 5mm Microfit	08566316	Straight Connector - 12mm Microfit
08566320	Endstop Connector - 5mm Microfit	08566326	Endstop Connector - 12mm Microfit
08566312	Straight Connector - 7mm Microfit	08566337	Straight Connector - 12.7mm Microfit
08566322	Endstop Connector - 7mm Microfit	08566338	Endstop Connector - 12.7mm Microfit
08566335	Straight Connector - 8mm Microfit	08566318	Straight Connector - 14mm Microfit
08566336	Endstop Connector - 8mm Microfit	08566328	Endstop Connector - 14mm Microfit
08566313	Straight Connector - 8.5mm Microfit	08566319	Straight Connector - 16mm Microfit
08566323	Endstop Connector - 8.5mm Microfit	08566329	Endstop Connector - 16mm Microfit
08566315	Straight Connector - 10mm Microfit	08566333	Straight Connector - 18mm Microfit
08566325	Endstop Connector - 10mm Microfit	08566334	Endstop Connector - 18mm Microfit

Available Locally From: